


LED panel**Pro Office 625x625 mm, 17 W, 3,000 K, white****Special features**

- Eligible for BEG German federal funding for energy-efficient buildings
- For insertion into grid ceilings
- Can be installed in surface-mount or flush-mount frames
- Highly efficient solution
- Renovation solution for T5/T8 louver lights
- Suitable for office spaces/reception rooms/hallways
- Suitable for workplaces with screens in accordance with EN 12464-1 BAP65

Housing Material	Aluminium
Housing Color	White
Material of Lens	Plastic
Suitable for Computer Workstations	Yes
Mounting Type	Installation mounting
Mounting Location	Inside
Mounting Area	Ceiling installation
Protection Class	Protection class III/safety extra-low voltage
Operating Mode	Constant current
Rated Input	17 W
Rated Power Consumption Standby	0.5 W
Rated Input Voltage	35-40 V/DC
Rated Current	450 mA
Power Supply Unit incl.	No
Dimmable	Yes
Control	Dimmable via optional power supply unit
Motion Detector	No

Light Source	LED, Light source not changeable
Color Temperature	3000 K
Colour Consistency	3 SDCM
Colour consistency light source	3 SDCM
CRI (Ra)	80
Rated Luminous Flux	2880 lm
Luminous Efficiency	169.4 lm/W
Rated Angle of Reflection	90 Degree
UGR	19
Distribution Characteristic 120°	DLS

Light Exit Surfaces	1
Light characteristics	Direct

Light direction	Below
Length	620 mm
Width	620 mm
Height	32 mm
Product weight	2165 g
IP Protection Class	IP 50
IK Protection Class	IK03
Life Time L80 / B50	50000 h
Switching Cycles	100000
Power Consumption	17 kWh/1000h
EEI	D

